

## Data sheet

- (R118839300)

### Technical data

<b>Order no.</b>	<b>R118839300</b>
------------------	-------------------

Type	-
------	---

### General information

Note	-
------	---

Features	Output expansion unit 2x2 enabling current paths, 2x1 signalling outputs DC 24 V screw-terminals pluggable
----------	--

### Safety

Safety requirements	SIL CL 3, PL e, Kat 4
---------------------	-----------------------

Implementation of the electrical connection	-
---	---

Power supply (rated value)	DC 24 V
----------------------------	---------

Power supply (permitted range)	-
--------------------------------	---

Power loss	1.4 W
------------	-------

### Output circuit Relais

Number enabling current path	4
------------------------------	---

Number signaling current path	2
-------------------------------	---

	6 A
--	-----

	2 A
--	-----

Utilization category AC-15	Ue 230 V, Ie 3 A
----------------------------	------------------

Utilization category DC-13	Ue 24 V, Ie 1 A
----------------------------	-----------------

Number of operating cycle of relay outputs	10 <sup>7</sup>
--	-----------------

Max. peak current at control inputs	110 mA
-------------------------------------	--------

Certifications	-
----------------	---

UL certification	yes
------------------	-----

### Housing

Material	PC
----------	----

Mounting	Profile rail 35 mm
----------	--------------------

### Mechanical data

Dimensions (WxHxD)	22.5 mm x 96.5 mm x 114 mm
--------------------	----------------------------

Weight	180 g
--------	-------

### Environmental conditions

Operating temperature	-25 °C to 65 °C
-----------------------	-----------------

Storage temperature	-25 °C to 70 °C
---------------------	-----------------

### Certifications

UL certification	yes
------------------	-----

KC certification	-
------------------	---