

**Data sheet**
**VIPA CPU 115 - Micro CPU (115-6BL04)**
**Technical data**

<b>Order no.</b>	<b>115-6BL04</b>
Type	VIPA CPU 115 - Micro CPU
<b>General information</b>	
Note	-
Features	Work memory [KB]: 32 Onboard 16x DI / 12x DO / 4x DIO / 2x Counter / 2x PWM Interface [MP <sup>2</sup> I]: MPI MMC card slot, up to 4 modules stackable (100V or 200V) Programmable with WinPLC7(lite) and SIMATIC Manager WinPLC7(lite) please order separate SW211K2OD
<b>Technical data power supply</b>	
Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	yes
Current consumption (no-load operation)	90 mA
Current consumption (rated value)	1 A
Inrush current	58 A
$I^2t$	0.38 A <sup>2</sup> s
Max. current drain at backplane bus	0.8 A
Max. current drain load supply	-
Power loss	8.5 W
Reverse polarity protection	yes
<b>Technical data digital inputs</b>	
Number of inputs	16 (20)
Cable length, shielded	1000 m
Cable length, unshielded	600 m
Rated load voltage	DC 24 V
Reverse polarity protection of rated load voltage	yes
Current consumption from load voltage L+ (without load)	-
Rated value	DC 24 V
Input voltage for signal "0"	DC 0...5 V
Input voltage for signal "1"	DC 15...28.8 V
Signal logic input	Sinking input
Input current for signal "1"	7 mA
Connection of Two-Wire-BEROs possible	yes
Max. permissible BERO quiescent current	1.5 mA
Input delay of "0" to "1"	3 ms
Input delay of "1" to "0"	3 ms
Input characteristic curve	IEC 61131-2, type 1
Initial data size	3 Byte
<b>Technical data digital outputs</b>	
Number of outputs	16 (12)
Cable length, shielded	1000 m
Cable length, unshielded	600 m

Rated load voltage	DC 24 V
Reverse polarity protection of rated load voltage	-
Current consumption from load voltage L+ (without load)	50 mA
Total current per group, horizontal configuration, 40°C	4 A
Total current per group, horizontal configuration, 60°C	4 A
Total current per group, vertical configuration	4 A
Output voltage signal "1" at min. current	L+ (-125 mV)
Output voltage signal "1" at max. current	L+ (-0.8 V)
Output current at signal "1", rated value	0.5 A
Output delay of "0" to "1"	max. 100 µs
Output delay of "1" to "0"	max. 350 µs
Minimum load current	-
Lamp load	5 W
Switching frequency with resistive load	max. 1000 Hz
Switching frequency with inductive load	max. 0.5 Hz
Switching frequency on lamp load	max. 10 Hz
Internal limitation of inductive shut-off voltage	L+ (-52 V)
Short-circuit protection of output	yes, electronic
Trigger level	1 A
Output data size	3 Byte

#### Technical data counters

Number of counters	4
Counter width	32 Bit
Maximum input frequency	30 kHz
Maximum count frequency	30 kHz
Mode incremental encoder	yes
Mode pulse / direction	yes
Mode pulse	yes
Mode frequency counter	-
Mode period measurement	-
Gate input available	yes
Latch input available	-
Reset input available	-
Counter output available	-

#### Status information, alarms, diagnostics

Status display	yes
Interrupts	yes
Process alarm	yes
Diagnostic interrupt	yes
Diagnostic functions	no
Diagnostics information read-out	possible
Supply voltage display	green LED
Group error display	red SF LED
Channel error display	none

#### Isolation

Between channels of groups to	8
Between channels and backplane bus	yes
Insulation tested with	DC 500 V

**PWM data**

PWM channels	2
PWM time basis	PWM 0.1ms/1ms / HF-PWM 2.5...50kHz
Period length	-
Minimum pulse width	PWM 1...60000 * Time base / HF-PWM 4...60000µs
Type of output	Highside

**Load and working memory**

Load memory, integrated	40 KB
Load memory, maximum	40 KB
Work memory, integrated	32 KB
Work memory, maximal	32 KB
Memory divided in 50% program / 50% data	-
Memory card slot	MMC-Card with max. 512 MB

**Hardware configuration**

Racks, max.	1
Modules per rack, max.	4
Number of integrated DP master	-
Number of DP master via CP	4
Operable function modules	4
Operable communication modules PtP	4
Operable communication modules LAN	-

**Status information, alarms, diagnostics**

Status display	yes
Interrupts	yes
Process alarm	yes
Diagnostic interrupt	yes
Diagnostic functions	no
Diagnostics information read-out	possible
Supply voltage display	green LED
Group error display	red SF LED
Channel error display	none

**Command processing times**

Bit instructions, min.	0.25 µs
Word instruction, min.	1.2 µs
Double integer arithmetic, min.	2.6 µs
Floating-point arithmetic, min.	50 µs

**Timers/Counters and their retentive characteristics**

Number of S7 counters	256
S7 counter remanence	adjustable 0 up to 64
S7 counter remanence adjustable	C0 .. C7
Number of S7 times	256
S7 times remanence	adjustable 0 up to 128
S7 times remanence adjustable	not retentive

**Data range and retentive characteristic**

Number of flags	8192 Bit
-----------------	----------

Bit memories retentive characteristic adjustable	adjustable 0 up to 256
Bit memories retentive characteristic preset	MB0 .. MB15
Number of data blocks	2047
Max. data blocks size	16 KB
Number range DBs	1 ... 2047
Max. local data size per execution level	1024 Byte
Max. local data size per block	1024 Byte

### Blocks

Number of OBs	14
Maximum OB size	16 KB
Total number DBs, FBs, FCs	-
Number of FBs	1024
Maximum FB size	16 KB
Number range FBs	0 ... 1023
Number of FCs	1024
Maximum FC size	16 KB
Number range FCs	0 ... 1023
Maximum nesting depth per priority class	8
Maximum nesting depth additional within an error OB	1

### Time

Real-time clock buffered	yes
Clock buffered period (min.)	30 d
Type of buffering	Vanadium Rechargeable Lithium Battery
Load time for 50% buffering period	20 h
Load time for 100% buffering period	48 h
Accuracy (max. deviation per day)	10 s
Number of operating hours counter	8
Clock synchronization	-
Synchronization via MPI	-
Synchronization via Ethernet (NTP)	-

### Address areas (I/O)

Input I/O address area	1024 Byte
Output I/O address area	1024 Byte
Process image adjustable	-
Input process image preset	128 Byte
Output process image preset	128 Byte
Input process image maximal	128 Byte
Output process image maximal	128 Byte
Digital inputs	8192
Digital outputs	8192
Digital inputs central	148
Digital outputs central	144
Integrated digital inputs	16 (20)
Integrated digital outputs	16 (12)
Analog inputs	512
Analog outputs	512
Analog inputs, central	32
Analog outputs, central	16

Integrated analog inputs	-
Integrated analog outputs	-

### Communication functions

PG/OP channel	yes
Global data communication	yes
Number of GD circuits, max.	4
Size of GD packets, max.	22 Byte
S7 basic communication	yes
S7 basic communication, user data per job	76 Byte
S7 communication	yes
S7 communication as server	yes
S7 communication as client	-
S7 communication, user data per job	160 Byte
Number of connections, max.	16

### Functionality Sub-D interfaces

Type	MP2I
Type of interface	RS485
Connector	Sub-D, 9-pin, female
Electrically isolated	-
MPI	yes
MP2I (MPI/RS232)	yes
Point-to-point interface	-
5V DC Power supply	max. 90mA, non-isolated
24V DC Power supply	max. 100mA, non-isolated

### Functionality MPI

Number of connections, max.	16
PG/OP channel	yes
Routing	-
Global data communication	yes
S7 basic communication	yes
S7 communication	yes
S7 communication as server	yes
S7 communication as client	-
Transmission speed, min.	19.2 kbit/s
Transmission speed, max.	187.5 kbit/s

### Housing

Material	PPE / PA 6.6
Mounting	Profile rail 35 mm

### Mechanical data

Dimensions (WxHxD)	152.4 mm x 76 mm x 48 mm
Net weight	292 g
Weight including accessories	-
Gross weight	-

### Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

**Certifications**

UL certification	yes
KC certification	-