

Data sheet

PS 207 (207-1BA00)


Technical data

Order no.	207-1BA00
Type	PS 207

General information

Note	-
Features	AC 100...240 V w/o manual intervention Output voltage DC 24 V

Technical data power supply

Input voltage (rated value)	AC 100...240 V
Input voltage (permitted range)	AC 100...240 V
Mains frequency (rated value)	50...60 Hz
Mains frequency (permitted range)	47...63 Hz
Input current (at 120 V)	0.53 A
Input current (at 230 V)	0.24 A
Inrush current (at 25 °C)	30 A
Power consumption typ.	53 W
Output voltage (rated value)	24 V
Output current (rated value)	2 A
Power supply parallel switchable	
Protect type	Short circuit, overload, over temperature
Ripple of output voltage (max.), BW=20 MHz	100 mV
Efficiency typ.	90 %
Power loss typ.	5 W

Clamp parameter

Terminal voltage max.	-
Terminal current max.	-

Status information, alarms, diagnostics

Status display	yes
Interrupts	no
Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	no
Diagnostics information read-out	none
Supply voltage display	none
Group error display	none
Channel error display	none

Housing

Material	PPE / PA 6.6
Mounting	Profile rail 35 mm

Mechanical data

Dimensions (WxHxD)	25.4 mm x 76 mm x 78 mm
--------------------	-------------------------

Weight	150 g
--------	-------

Environmental conditions

Operating temperature	0 °C to 60 °C
-----------------------	---------------

Storage temperature	-25 °C to 70 °C
---------------------	-----------------

Certifications

UL508 certification	-
---------------------	---