

## Data sheet

### SM 222 (222-1HD20)

#### Technical data

<b>Order no.</b>	<b>222-1HD20</b>
Type	SM 222
<b>General information</b>	
Note	-
Features	4 isolated relay outputs AC 230 V/ DC 30 V Output current 16 A
<b>Current consumption/power loss</b>	
Current consumption from backplane bus	200 mA
Power loss	2 W
<b>Technical data digital outputs</b>	
Number of outputs	4
Cable length, shielded	1000 m
Cable length, unshielded	600 m
Rated load voltage	AC 230 V
Current consumption from load voltage L+ (without load)	-
Total current per group, horizontal configuration, 40°C	16 A
Total current per group, horizontal configuration, 60°C	16 A
Total current per group, vertical configuration	16 A
Output current at signal "1", rated value	16 A
Output delay of "0" to "1"	10 ms
Output delay of "1" to "0"	10 ms
Minimum load current	-
Lamp load	-
Parallel switching of outputs for redundant control of a load	not possible
Parallel switching of outputs for increased power	not possible
Actuation of digital input	-
Switching frequency with resistive load	max. 10 Hz
Switching frequency with inductive load	-
Switching frequency on lamp load	-
Internal limitation of inductive shut-off voltage	-
Short-circuit protection of output	-
Trigger level	-
Number of operating cycle of relay outputs	10 <sup>7</sup>
Switching capacity of contacts	16 A
Output data size	1 Byte
<b>Status information, alarms, diagnostics</b>	
Status display	none
Interrupts	no
Process alarm	no
Diagnostic interrupt	no

Diagnostic functions	no
Diagnostics information read-out	none
Supply voltage display	none
Group error display	none
Channel error display	none

### Isolation

Between channels	✓
Between channels of groups to	1
Between channels and backplane bus	✓
Insulation tested with	DC 500 V

### Datasizes

Input bytes	0
Output bytes	1
Parameter bytes	0
Diagnostic bytes	0

### Housing

Material	PPE / PA 6.6
Mounting	Profile rail 35 mm

### Mechanical data

Dimensions (WxHxD)	25.4 mm x 76 mm x 88 mm
Weight	120 g

### Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

### Certifications

UL508 certification	yes
---------------------	-----