

Data sheet
SM 238C, Digital In-/Output, Counter, Analog In-/Output (238-2BC00)
Technical data

Order no.	238-2BC00
Type	SM 238C, Digital In-/Output, Counter, Analog In-/Output

General information

Note	-
Features	16 (12)x DI, DC 24 V 0 (4)x DO, DC 24 V, 1 A Up to 3x Counter up to 30 kHz 4x AI 12 Bit 3x voltage, current 1x RTD 2x AO 12 Bit voltage, current

Current consumption/power loss

Current consumption from backplane bus	280 mA
Power loss	5.5 W

Technical data digital inputs

Number of inputs	16
Cable length, shielded	1000 m
Cable length, unshielded	600 m
Rated load voltage	-
Current consumption from load voltage L+ (without load)	-
Rated value	DC 20.4...28.8 V
Input voltage for signal "0"	DC 0...5 V
Input voltage for signal "1"	DC 15...28.8 V
Input voltage hysteresis	-
Frequency range	-
Input resistance	-
Input current for signal "1"	7 mA
Connection of Two-Wire-BEROs possible	yes
Max. permissible BERO quiescent current	1.5 mA
Input delay of "0" to "1"	3 ms
Input delay of "1" to "0"	3 ms
Number of simultaneously utilizable inputs horizontal configuration	16
Number of simultaneously utilizable inputs vertical configuration	16
Input characteristic curve	IEC 61131-2, type 1
Initial data size	16 Byte

Technical data digital outputs

Number of outputs	4
Cable length, shielded	1000 m
Cable length, unshielded	600 m
Rated load voltage	DC 20.4...28.8 V
Reverse polarity protection of rated load voltage	-
Current consumption from load voltage L+ (without load)	20 mA
Total current per group, horizontal configuration, 40°C	4 A

Total current per group, horizontal configuration, 60°C	2 A
Total current per group, vertical configuration	4 A
Output voltage signal "1" at min. current	L+ (-125 mV)
Output voltage signal "1" at max. current	L+ (-0.8 V)
Output current at signal "1", rated value	1 A
Output delay of "0" to "1"	150 µs
Output delay of "1" to "0"	100 µs
Minimum load current	-
Lamp load	5 W
Parallel switching of outputs for redundant control of a load	not possible
Parallel switching of outputs for increased power	not possible
Actuation of digital input	yes
Switching frequency with resistive load	max. 1000 Hz
Switching frequency with inductive load	max. 0.5 Hz
Switching frequency on lamp load	max. 10 Hz
Internal limitation of inductive shut-off voltage	L+ (-52 V)
Short-circuit protection of output	yes, electronic
Trigger level	1.5 A
Number of operating cycle of relay outputs	-
Switching capacity of contacts	-
Output data size	16 Byte

Technical data analog inputs

Number of inputs	4
Cable length, shielded	200 m
Rated load voltage	DC 24 V
Reverse polarity protection of rated load voltage	yes
Current consumption from load voltage L+ (without load)	70 mA
Voltage inputs	yes
Min. input resistance (voltage range)	120 kOhm
Input voltage ranges	+1 V ... +5 V 0 V ... +10 V -10 V ... +10 V -400 mV ... +400 mV -4 V ... +4 V
Operational limit of voltage ranges	+/-0.3% ... +/-0.7%
Operational limit of voltage ranges with SFU	-
Basic error limit voltage ranges with SFU	+/-0.2% ... +/-0.5%
Basic error limit voltage ranges with SFU	-
Destruction limit voltage	max. 15V
Current inputs	yes
Max. input resistance (current range)	90 Ohm
Input current ranges	+4 mA ... +20 mA 0 mA ... +20 mA -20 mA ... +20 mA
Operational limit of current ranges	+/-0.3% ... +/-0.8%
Operational limit of current ranges with SFU	-
Basic error limit current ranges	+/-0.2% ... +/-0.5%
Radical error limit current ranges with SFU	-
Destruction limit current inputs (electrical current)	max. 50mA
Destruction limit current inputs (voltage)	max. 15V
Resistance inputs	yes

Resistance ranges	0 ... 600 Ohm 0 ... 3000 Ohm
Operational limit of resistor ranges	+/-0.4%
Operational limit of resistor ranges with SFU	-
Basic error limit	+/-0.2%
Basic error limit with SFU	-
Destruction limit resistance inputs	max. 15V
Resistance thermometer inputs	yes
Resistance thermometer ranges	Pt100 Pt1000 Ni100 Ni1000
Operational limit of resistance thermometer ranges	+/-0.4% ... +/-1.0%
Operational limit of resistance thermometer ranges with SFU	-
Basic error limit thermoresistor ranges	+/-0.2% ... +/-0.5%
Basic error limit thermoresistor ranges with SFU	-
Destruction limit resistance thermometer inputs	max. 15V
Thermocouple inputs	-
Thermocouple ranges	-
Operational limit of thermocouple ranges	-
Operational limit of thermocouple ranges with SFU	-
Basic error limit thermoelement ranges	-
Basic error limit thermoresistor ranges with SFU	-
Destruction limit thermocouple inputs	-
Programmable temperature compensation	-
External temperature compensation	-
Internal temperature compensation	-
Temperature error internal compensation	-
Technical unit of temperature measurement	°C
Resolution in bit	16
Measurement principle	Sigma-Delta
Basic conversion time	7 ms - 272 ms
Noise suppression for frequency	50 Hz and 60 Hz
Initial data size	8 Byte

Technical data analog outputs

Number of outputs	2
Cable length, shielded	200 m
Rated load voltage	DC 24 V
Reverse polarity protection of rated load voltage	yes
Current consumption from load voltage L+ (without load)	70 mA
Voltage output short-circuit protection	yes
Voltage outputs	yes
Min. load resistance (voltage range)	1 kOhm
Max. capacitive load (current range)	1 µF
Max. inductive load (current range)	30 mA
Output voltage ranges	-10 V ... +10 V +1 V ... +5 V 0 V ... +10 V
Operational limit of voltage ranges	+/-0.4% ... +/-0.8%
Basic error limit voltage ranges with SFU	+/-0.2% ... +/-0.4%
Destruction limit against external applied voltage	max. 15V

Current outputs	yes
Max. in load resistance (current range)	500 Ohm
Max. inductive load (current range)	10 mH
Typ. open circuit voltage current output	13 V
Output current ranges	-20 mA ... +20 mA 0 mA ... +20 mA 0 mA ... +20 mA
Operational limit of current ranges	+/-0.3% ... +/-0.8%
Radical error limit current ranges with SFU	+/-0.2% ... +/-0.5%
	max. 15V
Settling time for ohmic load	0.3 ms
Settling time for capacitive load	1 ms
Settling time for inductive load	0.5 ms
Resolution in bit	12
Conversion time	1.50 ms
Substitute value can be applied	yes
Output data size	4 Byte

Status information, alarms, diagnostics

Status display	yes
Interrupts	yes
Process alarm	yes, parameterizable
Diagnostic interrupt	yes, parameterizable
Diagnostic functions	yes
Diagnostics information read-out	possible
Supply voltage display	green LED per group
Group error display	red SF LED
Channel error display	none

Isolation

Between channels	-
Between channels of groups to	-
Between channels and backplane bus	yes
Between channels and power supply	yes
Max. potential difference between circuits	-
Max. potential difference between inputs (Ucm)	DC 4 V
Max. potential difference between Mana and Mintern (Uiso)	-
Max. potential difference between inputs and Mana (Ucm)	-
Max. potential difference between inputs and Mintern (Uiso)	DC 75 V/ AC 50 V
Max. potential difference between Mintern and outputs	-
Insulation tested with	DC 500 V

Datasizes

Input bytes	8 + 16
Output bytes	4 + 16
Parameter bytes	18 + 71
Diagnostic bytes	12 + 12

Housing

Material	PPE / PA 6.6
Mounting	Profile rail 35 mm

Mechanical data

Dimensions (WxHxD)	50.8 mm x 76 mm x 88 mm
Net weight	150 g
Weight including accessories	-
Gross weight	-

Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

Certifications

UL certification	yes
KC certification	-