



## Data sheet

### IM 253DPO, PROFIBUS-DP slave (253-1DP11)

#### Technical data

<b>Order no.</b>	<b>253-1DP11</b>
Type	IM 253DPO, PROFIBUS-DP slave
<b>General information</b>	
Note	-
Features	PROFIBUS-DP slave (DP-V0, DP-V1) For max. 32 peripheral modules (16 analog) 244 Byte input and 244 Byte output data
<b>Technical data power supply</b>	
Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	
Current consumption (no-load operation)	70 mA
Current consumption (rated value)	1 A
Inrush current	65 A
$I_{\Delta t}$	0.85 A <sup>2</sup> s
Max. current drain at backplane bus	3.5 A
Max. current drain load supply	-
Power loss	2.5 W
<b>Status information, alarms, diagnostics</b>	
Status display	yes
Interrupts	yes, parameterizable
Process alarm	yes, parameterizable
Diagnostic interrupt	yes, parameterizable
Diagnostic functions	yes, parameterizable
Diagnostics information read-out	possible
Supply voltage display	green LED
Service Indicator	-
Group error display	red SF LED
Channel error display	none
<b>Hardware configuration</b>	
Racks, max.	1
Modules per rack, max.	32
Number of digital modules, max.	32
Number of analog modules, max.	16
<b>Communication</b>	
Fieldbus	PROFIBUS-DP to EN 50170
Type of interface	FOC
Connector	2-pin FOC POF/HCS
Topology	Line structure with two-wire FOC
Electrically isolated	

Number of participants, max.	125
Node addresses	1 - 99
Transmission speed, min.	9.6 kbit/s
Transmission speed, max.	12 Mbit/s
Address range inputs, max.	244 Byte
Address range outputs, max.	244 Byte
Number of TxPDOs, max.	-
Number of RxPDOs, max.	-

### Housing

Material	PPE / PA 6.6
Mounting	Profile rail 35 mm

### Mechanical data

Dimensions (WxHxD)	25.4 mm x 76 mm x 78 mm
Weight	110 g

### Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

### Certifications

UL508 certification	yes
---------------------	-----