

Data sheet

IM 261, Row interface (261-1CA00)

Technical data

Order no.	261-1CA00
Type	IM 261, Row interface
General information	
Note	-
Features	Only be used in conjunction with the PC 288 or a CPU
Technical data power supply	
Power supply (rated value)	-
Power supply (permitted range)	-
Reverse polarity protection	-
Current consumption (no-load operation)	-
Current consumption (rated value)	-
Inrush current	-
Max. current drain at backplane bus	1.5 A
Max. current drain load supply	-
Power loss	1 W
Status information, alarms, diagnostics	
Status display	yes
Interrupts	no
Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	no
Diagnostics information read-out	none
Supply voltage display	yes
Group error display	none
Channel error display	none
Hardware configuration	
Racks, max.	1
Modules per rack, max.	16
Number of digital modules, max.	16
Number of analog modules, max.	16
Housing	
Material	PPE
Mounting	Profile rail 35 mm
Mechanical data	
Dimensions (WxHxD)	25.4 mm x 76 mm x 78 mm
Weight	90 g
Environmental conditions	
Operating temperature	0 °C to 60 °C

Storage temperature -25 °C to 70 °C

Certifications

UL508 certification yes
