

## VIPA PROFINET-connector 972-0PN00/ 972-8PN00



### Product specification

- field plug Cat.6A with multiport capability
- suitable for 10 GBits as per IEEE 802.3an
- eight-core RJ45 plug (can be assembled in the field) for AWG 22
- AWG 26/7-22/7, AWG 24/1-22/1 can be connected
- solid copper wire diameter 0.4 to 0.64 mm
- stranded copper wire diameter 0.48 to 0.76 mm
- core diameters up to 1.6 mm
- overall cable diameter from 5.5 to 8.5 mm
- plug consists of only two parts
- easy assembly without special tools
- on assembly the cable is physically secured to the loader part
- easily fitted cable strain relief
- cable strain relief can be snapped on as color coding after assembly
- industry-compatible zinc die-cast housing
- protected latch
- can be used as a test plug on the IP67 side of variants 1, 4, 5, 6 and 14

# DATA SHEET



## Technical Data

### General data

Dimensions L x W x H	49.05 x 12.9 x 14.7 mm
Cu-Conductor diameter	
solid	0.40 - 0.64 mm AWG 24/1 - AWG 22/1
stranded	0.48 - 0.76 mm AWG 26/7 - AWG 22/7
Insulation diameter	0.85 - 1.6 mm
Cable diameter	5.5 - 8.5 mm

### Transmission Performance

Category	Cat.6 ANSI/TIA/EIA-568-B.2-10
----------	-------------------------------

### Standards

Generic cabling systems	ANSI/TIA/EIA-568-B.2-10 ISO/IEC 11801:2002 EN 50173-1:2007 ISO/IEC 24702:2006 DIN EN 61918 Draft 02.2007 IEC 60603-7-5
-------------------------	---

### Connector

UL Standard for Communication circuit Accessories	UL 1863
Degrees of protection provided by enclosures (IP code)	IEC 60529

### Mechanical properties

Insertion force	$\leq 30$ N
Life	$\geq 750$

### Material

Connector housing	GD-Zn purify
Basic housing	PA UL94-V0
Contact	Phosphor bronze
Contact surface	Gold plating over nickel plating
Shield	Brass
Shield surface	nickel plating
Cable strain relief	PA UL94-V0

### Protection against ingress

Particulate ingress	IP20
---------------------	------

### Climatic properties

Temperature range	-40 ° bis +70 °C
-------------------	------------------

### Electrical properties

Contact resistance	$\leq 20$ m $\Omega$
Insulation resistance	$\geq 500$ M $\Omega$
Voltage proof	
Contact - contact	$\geq 1000$ V DC
Contact - shield	$\geq 1500$ V DC
Current carrying capacity at 50 °C	1 A

# DATA SHEET

## Dimensional drawing

