



Data sheet

Touch Panel TP 604LC+ (62E-MGC0-CB)


Technical data

Order no.	62E-MGC0-CB
Type	Touch Panel TP 604LC+
General information	
Note	-
Features	4.3", TFT, 480x272 Pixel Cortex-A8 processor, 667MHz 256 MB work memory, 128 MB user memory RS232, RS422/485, USB-A, Ethernet RJ45 (MPI/DP interface optional available) Windows Embedded CE 6.0 Professional, Runtime Movicon CE Standard
Display	
Display size (diagonal)	4.3 "
Display size (width)	95 mm
Display size (height)	54 mm
Resolution	272 x 480 / 480 x 272
Aspect ratio	16:9
Type of display	TFT color (64K colors)
MTBF Backlights (25°C)	30000 h
System properties	
Processor	Cortex-A8 667 MHz
Operating system	Windows CE 6.0 Prof.
User software	Movicon 11 CE Standard
Work memory	256 MB
User memory	128 MB
Available memory (user data)	50 MB
SD/MMC Slot	
CF Card Slot Typ II	-
CFast Slot	-
Time	
Real-time clock buffered	
Clock buffered period (min.)	26 w
Type of buffering	Manganese Rechargeable Lithium Battery
Load time for 50% buffering period	5 h
Load time for 100% buffering period	24 h
Accuracy (max. deviation per day)	2 s
Operating controls	
Touchscreen	resistive
Touch function	Single Touch
Keyboard	external via USB
Mouse	external via USB

Interfaces

MPI, PROFIBUS-DP	optional
MPI, PROFIBUS-DP connector	-
Serial, COM1	RS232
COM1 connector	Sub-D, 9-pin, male
Serial, COM2	RS232 / RS422 / RS485
COM2 connector	Sub-D, 25-pin, female
Number of USB-A interfaces	1
USB-A connector	USB-A (host)
Number of USB-B interfaces	-
USB-B connector	-
Number of ethernet interfaces	1
Ethernet	Ethernet 10/100 MBit
Ethernet connector	RJ45
Integrated ethernet switch	-
Video connectors	-
Audio connections	-

Technical data power supply

Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	
Current consumption (no-load operation)	0.16 A
Current consumption (rated value)	0.3 A
Inrush current	75 A
I^2t	0.36 A ² s
Power loss	6 W

Status information, alarms, diagnostics

Supply voltage display	none
------------------------	------

Mechanical data

Housing / Protection type

Material	PC
Mounting	mounting clips
Protect type front side	IP 65
Protect type back side	IP 20

Dimensions

Front panel	140 mm x 116 mm x 6 mm
Rear panel	122 mm x 98 mm x 51 mm

Installation cut-out

Width	123 mm
Height	99 mm
Minimum	2.5 mm
Maximum front panel thickness	6 mm
Weight	500 g

Environmental conditions

Operating temperature	0 °C to 50 °C
Storage temperature	-20 °C to 60 °C

Certifications

UL508 certification	yes
---------------------	-----