

Data sheet

Touch Panel TP 606C (62G-FID0-CB)

Technical data

Order no.	62G-FID0-CB
------------------	--------------------

Type	Touch Panel TP 606C
------	---------------------

General information

Note	-
------	---

Features	Display: 6.5" Processor: XScale-CPU 1066 MHz RAM [MB]: 256 User memory [MB]: 512 External slot: SD Card CF Card Onboard Interface: 1x RS232 1x 422/485 1x USB-A 1x USB-B 1x RJ45 (Ethernet) 1x MPI/PROFIBUS-DP Software: CE6.0 Professional Movicon 11 CE Standard
----------	--

Display

Display size (diagonal)	6.5 "
-------------------------	-------

Display size (width)	132.5 mm
----------------------	----------

Display size (height)	99.4 mm
-----------------------	---------

Resolution	480 x 640 / 640 x 480
------------	-----------------------

Aspect ratio	4:3
--------------	-----

Type of display	TFT color (16.7M colors)
-----------------	--------------------------

MTBF Backlights (25°C)	50000 h
------------------------	---------

System properties

Processor	Xscale 1.1 GHz
-----------	----------------

Operating system	Windows CE 6.0 Prof.
------------------	----------------------

User software	Movicon 11 CE Standard
---------------	------------------------

Work memory	256 MB
-------------	--------

User memory	512 MB
-------------	--------

Available memory (user data)	380 MB
------------------------------	--------

SD/MMC Slot	yes
-------------	-----

CF Card Slot Typ II	yes
---------------------	-----

CFast Slot	-
------------	---

Time

Real-time clock buffered	yes
--------------------------	-----

Clock buffered period (min.)	6 w
------------------------------	-----

Type of buffering	Vanadium Rechargeable Lithium Battery
-------------------	---------------------------------------

Load time for 50% buffering period	10 h
------------------------------------	------

Load time for 100% buffering period	48 h
-------------------------------------	------

Accuracy (max. deviation per day)	10 s
-----------------------------------	------

Operating controls

Touchscreen	resistive
-------------	-----------

Touch function	Single Touch
----------------	--------------

Keyboard	external via USB
----------	------------------

Mouse	external via USB
-------	------------------

Interfaces

MPI, PROFIBUS-DP	RS485 isolated
------------------	----------------

MPI, PROFIBUS-DP connector	Sub-D, 9-pin, female
----------------------------	----------------------

Serial, COM1	RS232
COM1 connector	Sub-D, 9-pin, male
Serial, COM2	RS422/485 isolated
COM2 connector	Sub-D, 9-pin, female
Number of USB-A interfaces	1
USB-A connector	USB-A (host)
Number of USB-B interfaces	1
USB-B connector	USB-B (device)
Number of ethernet interfaces	1
Ethernet	Ethernet 10/100 MBit
Ethernet connector	RJ45
Integrated ethernet switch	-
Video connectors	-
Audio connections	-

Technical data power supply

Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	yes
Current consumption (no-load operation)	0.34 A
Current consumption (rated value)	0.5 A
Inrush current	6 A
I^2t	0.2 A ² s
Power loss	8.2 W

Status information, alarms, diagnostics

Status display	none
Supply voltage display	yes

Mechanical data

Housing / Protection class

Material	die-cast aluminum
Mounting	via integrated pivoted lever
Protection class IP front side	IP 65
Protection class IP back side	IP 20
Protection class NEMA front side	-
Protection class NEMA back side	-

Dimensions

Front panel	212 mm x 156 mm x 7.5 mm
Rear panel	198 mm x 142 mm x 37 mm

Installation cut-out

Width	200 mm
Height	144 mm
Minimum	2.5 mm
Maximum front panel thickness	6 mm
Net weight	1614 g
Weight including accessories	-
Gross weight	-

Environmental conditions

Operating temperature	0 °C to 50 °C
Storage temperature	-20 °C to 60 °C

Certifications

UL certification	yes
KC certification	-