

Data sheet

Panel PC PPC015 CE (67P-RRJ0-EB)

Technical data

Order no.	67P-RRJ0-EB
------------------	--------------------

Type	Panel PC PPC015 CE
------	--------------------

General information

Note	-
------	---

Features	Display: 15.6" Processor: Intel Celeron J1900 quad core @2 GHz Work memory: 2 GB Operating system and user memory: 2 GB Memory card plug-in place: CFast Interfaces: 2x Ethernet (10/100/1000), 2x USB 2.0, 1x USB 3.0, 2x serial (RS232,RS422/RS485), 1x VGA, Audio out Software: WEC7 Visualization system: Movicon 11.6 Runtime
----------	--

Display

Display size (diagonal)	15.6 "
-------------------------	--------

Display size (width)	344 mm
----------------------	--------

Display size (height)	195 mm
-----------------------	--------

Resolution	768 x 1366 / 1366 x 768
------------	-------------------------

Aspect ratio	16:9
--------------	------

Type of display	TFT color (16.7M colors)
-----------------	--------------------------

MTBF Backlights (25°C)	50000 h
------------------------	---------

System properties

Processor	Intel Celeron Quad core 2 GHz
-----------	-------------------------------

Operating system	Windows Embedded Compact 7
------------------	----------------------------

User software	Movicon 11 CE Standard
---------------	------------------------

Work memory	2 GB
-------------	------

User memory	2 GB
-------------	------

Available memory (user data)	1600 MB
------------------------------	---------

SD/MMC Slot	-
-------------	---

CF Card Slot Typ II	-
---------------------	---

CFast Slot	yes
------------	-----

Time

Real-time clock buffered	yes
--------------------------	-----

Clock buffered period (min.)	4 y
------------------------------	-----

Type of buffering	lithium battery
-------------------	-----------------

Load time for 50% buffering period	-
------------------------------------	---

Load time for 100% buffering period	-
-------------------------------------	---

Accuracy (max. deviation per day)	10 s
-----------------------------------	------

Operating controls

Touchscreen	PCAP
-------------	------

Touch function	Dual Touch
----------------	------------

Keyboard	external via USB
----------	------------------

Mouse	external via USB
-------	------------------

Interfaces

MPI, PROFIBUS-DP	-
------------------	---

MPI, PROFIBUS-DP connector	-
----------------------------	---

Serial, COM1	RS232 / RS422 / RS485
COM1 connector	Sub-D, 9-pin, male
Serial, COM2	RS232 / RS422 / RS485
COM2 connector	Sub-D, 9-pin, male
Number of USB-A interfaces	3
USB-A connector	USB-A (host)
Number of USB-B interfaces	-
USB-B connector	-
Number of ethernet interfaces	2
Ethernet	Ethernet 10/100/1000 MBit
Ethernet connector	2 x RJ45
Integrated ethernet switch	-
Video connectors	VGA SubD HD15
Audio connections	Line out, stereo jack 3.5 mm

Technical data power supply

Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	yes
Current consumption (no-load operation)	1.2 A
Current consumption (rated value)	1.3 A
Inrush current	1.3 A
I^2t	0.35 A ² s
Power loss	32 W

Status information, alarms, diagnostics

Status display	none
Supply voltage display	none

Mechanical data

Housing / Protection class

Material	coated aluminium steel plate
Mounting	via integrated pivoted lever
Protection class IP front side	IP 66
Protection class IP back side	IP 20
Protection class NEMA front side	-
Protection class NEMA back side	-

Dimensions

Front panel	417.8 mm x 312.8 mm x 6.2 mm
Rear panel	396 mm x 291 mm x 57.6 mm

Installation cut-out

Width	401 mm
Height	296 mm
Minimum	3 mm
Maximum front panel thickness	12 mm
Net weight	6.2 kg
Weight including accessories	-
Gross weight	-

Environmental conditions

Operating temperature	-10 °C to 60 °C
Storage temperature	-20 °C to 75 °C

Certifications

UL certification	yes
KC certification	-