

**Data sheet**

TM-H Router VPN/HSUPA/Ethernet/MPI (900-2H682)

## Technical data

<b>Order no.</b>	<b>900-2H682</b>
Type	TM-H Router VPN/HSUPA/Ethernet/MPI
<b>General information</b>	
Note	-
Features	For remote maintenance via Talk2M VPN 4x RJ45 LAN 100 Mbit / s (integrated switch) 1x RJ45 WAN 100 Mbps 1x integrated GSM / HSPA Pentaband modem (WAN) 1x SUB-D 9-pin MPI / PROFIBUS up to 12 Mbit / s 1x digital input and output Alarm management Please order the antenna separately Alarm management via SMS & EMail
<b>Inputs and outputs</b>	
Inputs	-
Outputs	-
<b>Communication</b>	
serial port	-
LAN	4 x RJ45, 10/100 MBit/s Switch
WAN	1 x RJ45, 10/100 MBit/s
Modem type	HSUPA
<b>Router</b>	
Router functions	IP-Forwarding IP-Filter NAT Port-Forwarding Routing Table DHCP-Client
RAS	PPP Dial-In PPP Dial-Out Call-Back
<b>VPN</b>	
VPN mode	-
Talk2M	-
Gateway protocols	MPI PPI PROFIBUS ISO TCP Modbus TCP
<b>Services</b>	
Server services	FTP HTTP
Client Services	FTP SMTP NTP DYNDNS SNMP
<b>Data management</b>	
Custom Website	-

Project	web interface
Integrated protocols	MPI MPI PROFIBUS ISO TCP Modbus TCP
<b>Interrupts</b>	
Alarm message	E-Mail SMS SNMP FTP
Alarm	E-Mail Hardware I/O SMS PLC-variables SNMP system variables FTP
<b>Housing</b>	
Material	-
Mounting	Profile rail 35 mm
<b>Mechanical data</b>	
Dimensions (WxHxD)	39 mm x 129 mm x 108 mm
Net weight	480 g
Weight including accessories	-
Gross weight	-
<b>Environmental conditions</b>	
Operating temperature	-20 °C to 70 °C
Storage temperature	-
<b>Certifications</b>	
UL certification	-
KC certification	-